

# CRANE ARMS TYPE KT / KTH



**A crane arm increases the reach of the forklift truck**

- steel construction
- secured by chain to prevent slipping

### Extensible constructions

- extension arm is positioned inside the shell and can be extended in 8 steps to reach full length; locked in position using the pin provided
- 14 possible positions; 2 swivel hooks

### KT

- rigid construction

### KTH

- variable working height, can be fixed in each of the positions using the pin provided
- a choice of 3 angles: 15°, 30° or 45°

### Fixed-length constructions

- 5 possible positions; 1 swivel hook

### KT-K

- rigid construction

### KTH-K

- variable working height, can be fixed in each of the positions using the pin provided
- a choice of 3 angles: 15°, 30° or 45°

### Accessories

- hydraulic extension function (max. 1000 mm, for KT and KTH)



Hydraulic extension function (KTH)

KTH extended and at an elevated working height




KT-K



KTH-K at an elevated working height

Fork sleeve inside dimensions in mm



	A	B	C
KT 2,5/KT-K 2,5	106	184	84
KT 5,0/KT-K 5,0	116	184	84
KTH 2,5/KTH-K 2,5	156	184	84
KTH 5,0/KTH-K 5,0	166	184	84

	Position	1	2	3	4	5	6	7	8	9	10	11	12	13	14	Dimensions ltxwxh	Weight
	Distance in mm	710	1000	1290	1590	1870	2055	2255	2455	2655	2855	3055	3255	3455	3655	in mm	paint./galv. in kg
KT-K 2,5	Load capacity in kg	2500	2500	2500	1800	1400	-	-	-	-	-	-	-	-	-	2000 x 490 x 480	135 / 145
KT 2,5	Load capacity in kg	2500	2500	2500	1800	1400	1200	1050	950	850	770	700	650	600	560	2160 x 490 x 480	175 / 188
KT-K 5,0	Load capacity in kg	5000	3550	2750	2250	1950	-	-	-	-	-	-	-	-	-	2000 x 500 x 520	160 / 172
KT 5,0	Load capacity in kg	5000	3550	2750	2250	1950	1700	1550	1400	1300	1200	1150	1050	1000	950	2160 x 500 x 520	210 / 226
	Distance in mm	695	990	1285	1580	1825	2090	2290	2490	2690	2890	3090	3290	3490	3690		
KTH-K 2,5	Load capacity in kg	2500	2500	2500	1800	1400	-	-	-	-	-	-	-	-	-	2050 x 540 x 560	160 / 172
KTH 2,5	Load capacity in kg	2500	2500	2500	1800	1400	1200	1050	950	850	770	700	650	600	560	2200 x 540 x 560	203 / 218
KTH-K 5,0	Load capacity in kg	5000	3550	2750	2250	1950	-	-	-	-	-	-	-	-	-	2050 x 550 x 600	184 / 198
KTH 5,0	Load capacity in kg	5000	3550	2750	2250	1950	1700	1550	1400	1300	1200	1150	1050	1000	950	2200 x 550 x 600	235 / 253

**Remember to check the load capacity of the forklift truck in question!**

Finish:

RAL 2000

RAL 3000

RAL 5012

RAL 6011

RAL 7005

hot-dip galvanized